

OCEANWAVES

**WAMOS[®] II - WAVE AND
CURRENT MONITORING
SYSTEM**



REAL-TIME DECISION SUPPORT



MAXIMIZE OPERATIONAL WINDOWS

WaMoS® II is a proven radar-based wave and surface current monitoring system developed by OceanWaveS GmbH. In comparison to conventional wave rider buoys and current profiling devices that generate single point measurements, WaMoS® II offers the advantages of presenting this information for a broad area, and in a richer context.

WaMoS® II's measurements are constantly refreshed while a vessel is underway, providing real time data relevant to the local operational area as compared to conditions reported at a closest available point of reference. High definition images of wave fields combined with numerical data and intuitive graphical reporting keep the operator well informed in assessing environmental risk and identifying safe operational windows.

As a complement to an existing sensor or as a primary system, WaMoS® II provides higher fidelity information with comparable accuracy, at lower lifecycle costs.

PROVEN ACCURACY & RELIABILITY

In industry-sponsored trials, data comparisons between WaMoS® II and wave rider buoys have independently verified its accuracy as well as the additional value provided in monitoring a full 360° range. WaMoS® II is presently supporting operational decision making applications including: offshore construction, diver support, safe helideck operations, and navigation in extreme current and sea states. Long-term deployments on several unmanned, remote coastal installations monitoring wave action and coastal erosion attest to its reliability.




FIG:1 – Three month time series data comparing wave height measurements obtained by WaMoS® II and a wave rider buoy.

FIG:2 – 1D Frequency spectrum graph showing two clear energy peaks from two wave systems.





FIG:3 – A corresponding 2D frequency-direction spectrum indicating two wave systems, one coming from the North-North-West and one from the West.



NEW SIGMA S6 CONNECT

A new web-enabled interface allows external systems such as Google Earth Pro and GIS platforms to interface with the sigma S6 WaMoS® II System to display radar imaging, wave, surface current and HRC information.

WAMOS® II EARNS INTERNATIONAL RECOGNITION

OceanWaveS and WaMoS® II have a large and diverse reference list. As the acceptance of X-band radar as a wave and current measuring device gains international reference and citation, the reference list of applications of WaMoS® II continues to grow. Installations of WaMoS® II are found around the world. A partial list of installation sites includes Norway, Denmark, Germany, Thailand, China, Canada and the USA.

WAMOS® II HIGH RESOLUTION CURRENT DISPLAY

Showing an eddy in the current field at a harbour entrance

FIG:4 – Mean radar backscatter image overlaid by the surface currents.

FIG:5 – Corresponding bathymetry image.






FIG:6 – WAMOS® II DATA COMPARISON
Time series graph for significant wave height, current speed and current direction obtained by WaMoS® II (red) and ADCP (blue).

FIG:7




FIG:7 – WAMOS® II WAVE RADAR IMAGE
WaMoS® II radar image containing an ambiguous stripe-like wave pattern. Arrows indicate two wave systems were detected, one coming from the North-Northwest and one from the West.

WAVE AND SURFACE CURRENT PARAMETERS

WaMoS® II measures and displays all the essential wave field parameters including significant wave height (H_s), Peak wave period (T_p), Peak wave length (λ_p) Peak wave direction (θ_p) as well as surface current speed (U) and surface current direction (θ_d).

PERFORMANCE AND OPERATING RANGE

The operating range of WaMoS® II extends to 4.0 km depending on X-Band radar type and installation geometry. The average range for vessel-based installations is approximately 3.0 km. Requiring a minimum wind speed of 3 m/s and a minimum wave height of 0.5 m – 0.75 m, the system easily detects wave lengths from 15 m – 600 m and covers periods from 3 sec – 18 sec.

SEA STATE ALARMING

Sea state alarms can be set to trigger for three different conditions:

- when significant wave height exceeds a specified value;
- if peak wave lengths fall outside a specified range; or
- if the encounter angle between the wave system and the ship's course moves outside a specified range.

DATA SHARING AND RECORDING

Advanced recording capability enables operators to review and confirm conditions in the event of an incident or regulatory enquiry. WaMoS® II can be exported for integration in other data base, meteorological and environmental systems. It can also provide NMEA output to conning and decision support systems.

HIGH RESOLUTION CURRENT AND BATHYMETRY IMAGING

This optional functionality displays high resolution current (HRC) for deep and shallow waters, bathymetric measurements are available for water depths to 30 m. Surface current and bathymetry maps are generated in a grid structure by the HRC software.

PRACTICAL AND VERSATILE SOLUTIONS

sigma S6 WaMoS® II connects to most commercially available marine radars, enabling customers to extract additional value and effectiveness from their existing assets. Should it be required, Rutter provides the option of supplying a dedicated high performance radar as an input sensor. It is now possible to combine WaMoS® II with Rutter Inc. *sigma* S6 Oil Spill Detection, SeaFusion Data Integration, Ice Navigator™ and Small Target Surveillance systems.

OCEANWAVES WAVE AND CURRENT MONITORING SYSTEMS

Features and Options:

- High Resolution Current (HRC)
- Wave and Current Analysis and Wave Spectra (WaMoS)
- Screen Recording -Screen Shots (.jpg & .png) and Movie Files (.avi)
- Multiple Remote Clients
- Average Surface Current
- Shallow Water Bathymetry
- Sea State Alarms (3)
- Fixed Sites
- Moving Vessels
- *sigma* S6 Connect

Note: WaMoS® II accepts standard serial/network inputs from navigational instruments (NMEA 0183) including: AIS, wind anemometer, echo sounder, speed log, GPS, and gyrocompass.

Information about end user training, product support, product combinations, performance modelling, product references and reliability measures can be provided by e-mailing your request to info@oceanwaves.de

OceanWaveS GmbH is an authorized representative of Rutter Inc.



OceanWaveS GmbH
Hansekontor
Vor dem Bardowicker Tore 6b
D-21339 Lüneburg
Germany
Tel: +49-4131-699 58-0
Fax: +49-4131-699 58-29
E-Mail: info@oceanwaves.de

www.oceanwaves.de